


The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® DL XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 24 watts, luminous flux of 3600 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                   |             |
|-----------------------------------|-------------|
| Item no.                          | 1009951     |
| Number of different light outlets | 1           |
| IP Code                           | IP20        |
| Assembly                          | Recessed    |
| Assembly details                  | Ceiling     |
| Secondary power / voltage         | 700 mA      |
| Safety class                      | III         |
| Wattage                           | 24 W        |
| Minimum ambient temperature       | -20 °C      |
| Maximum ambient temperature       | 40 °C       |
| Lumen                             | 3600 lm     |
| Colour temperature                | 3000 Kelvin |
| Beam angle                        | 55 °        |
| Color                             | white/black |
| CRI                               | 90          |
| UGR ≤                             | 22          |
| Service life                      | 50000 h     |
| Risk Group                        | 1           |
| Height                            | 10.5 cm     |
| Diameter                          | 16 cm       |
| Net weight                        | 0.7 kg      |
| Gross weight                      | 0.75 kg     |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093861 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                   |
|---------|-----------------------------------|
| 1010698 | LED driver , 30W, 700 mA          |
| 1010706 | LED driver , 36W, 700 mA, DALI    |
| 1010694 | NUMINOS® XL , Elliptical diffuser |
| 1010692 | NUMINOS® XL , Prismatic diffuser  |
| 1010702 | LED driver , 30W, 700 mA, PHASE   |
| 1010693 | NUMINOS® XL , Frosted diffuser    |
| 1010691 | NUMINOS® XL , Honeycomb diffuser  |
| 1010133 | NUMINOS® XL , reflector, gold     |
| 1010134 | NUMINOS® XL , reflector, copper   |

|                       |         |
|-----------------------|---------|
| Shape of cut-out      | round   |
| Installation depth    | 10.5 cm |
| Installation diameter | 14.5 cm |