


NUMINOS® MOVE XL

Recessed ceiling light, 3000 K, $40^{\circ},$ IP20, round, black / white

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINO-S® MOVE DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 24 watts, luminous flux of 3600 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NU-MINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| Item no. | 1009994 |
|-----------------------------------|-------------------------|
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 700 mA |
| Safety class | III |
| Wattage | 24 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 3600 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 40 ° |
| Color | black/white |
| CRI | 90 |
| UGR≤ | 19 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 11.6 cm |
| Diameter | 19 cm |
| Net weight | 0.63 kg |
| | |



Light Source

| 2093861 | A D |
|-------------|---------------------------------------|
| Accessories | |
| 1010698 | LED driver , 30W, 700 mA |
| 1010706 | LED driver , 36W, 700 mA, DALI |
| 1010694 | NUMINOS® XL , Elliptical diffuser |
| 1010133 | NUMINOS® XL , reflector, gold |
| 1010692 | NUMINOS® XL , Prismatic diffuser |
| 1010702 | LED driver , 30W, 700 mA, PHASE |
| 1010693 | NUMINOS® XL , Frosted diffuser |
| 1010134 | NUMINOS® XL , reflector, copper |
| 1010691 | NUMINOS® XL , Honey- comb diffuser |

| Gross weight | 1 kg |
|-----------------------|---------|
| Shape of cut-out | round |
| Installation depth | 13 cm |
| Installation diameter | 17.5 cm |