


NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE XS recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1010031
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	900 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black/chrome
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	5.7 cm
Diameter	8 cm
Net weight	0.11 kg

Light Source

2093755	
---------	---

Accessories

1005614	NUMINOS® XS , frosted diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1005612	NUMINOS® XS , diffuser
1010699	LED driver , 10W, 200 mA, PHASE
1005615	NUMINOS® XS , black diffuser
1005613	NUMINOS® XS , transparent diffuser
1010126	NUMINOS® XS , reflector, copper
1010125	NUMINOS® XS , reflector, gold

Gross weight	0.21 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm