




NUMINOS® GIMBLE XS

Recessed ceiling light, 3000 K, 20°, IP20, round, white

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® GIMBLE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1010054
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	950 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	5.7 cm
Diameter	8 cm
Net weight	0.11 kg

Light Source

2093745		Gross weight	0.21 kg
Accessories		Shape of cut-out	round
1006136	Numinos® XS Reducing ring , round 160/70 mm white	Installation depth	8 cm
1006135	Numinos® XS Reducing ring , round 160/70 mm black	Installation diameter	6.8 cm
1005614	NUMINOS® XS , frosted diffuser	BIG WHITE Page	45
1010695	LED driver , 21W, 200 mA, DALI		
1010703	LED driver , 23W, 200 mA, DALI		
1005612	NUMINOS® XS , diffuser		
1010699	LED driver , 10W, 200 mA, PHASE		
1005615	NUMINOS® XS , black diffuser		
1006137	Numinos® XS Reducing ring , square 160/70 mm black		
1006138	Numinos® XS Reducing ring , square 160/70 mm white		
1005613	NUMINOS® XS , transparent diffuser		
1010126	NUMINOS® XS , reflector, copper		
1010125	NUMINOS® XS , reflector, gold		