


## NUMINOS® GIMBLE XS

**Recessed ceiling light, 4000 K, 40°, IP20, round, black / white**

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® GIMBLE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1010066                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| IP Code                           | IP20                    |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 200 mA                  |
| Safety class                      | III                     |
| Wattage                           | 6.9 W                   |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 1000 lm                 |
| Colour temperature                | 4000 Kelvin             |
| Beam angle                        | 40 °                    |
| Color                             | black/white             |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 5.7 cm                  |
| Diameter                          | 8 cm                    |
| Net weight                        | 0.11 kg                 |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 2093754 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                    |
|---------|------------------------------------|
| 1005614 | NUMINOS® XS , frosted diffuser     |
| 1010126 | NUMINOS® XS , reflector, copper    |
| 1010695 | LED driver , 21W, 200 mA, DALI     |
| 1010703 | LED driver , 23W, 200 mA, DALI     |
| 1005612 | NUMINOS® XS , diffuser             |
| 1010699 | LED driver , 10W, 200 mA, PHASE    |
| 1005615 | NUMINOS® XS , black diffuser       |
| 1010125 | NUMINOS® XS , reflector, gold      |
| 1005613 | NUMINOS® XS , transparent diffuser |

|                       |         |
|-----------------------|---------|
| Gross weight          | 0.21 kg |
| Shape of cut-out      | round   |
| Installation depth    | 8 cm    |
| Installation diameter | 6.8 cm  |