


FLATT II

Wall-mounted light, SENSOR, 2700 K, 10W, anthracite / brown

The FLATT II light range combines modern design with high functionality. The wall-mounted and bollard lights are ideal for accentuated façade and path lighting. With a sea air resistant coating, dark sky compliant light distribution (ULOR <2%), 2,700K warm white light and optional sensor technology, they offer flexible solutions for residential and HoReCa applications.



TECHNICAL DATA

Item no.	1010107
Number of different light outlets	2
IP Code	IP54
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Wall
Number of through-wires	10
Primary nominal voltage	100-240V ~50/60 Hz
Secondary power / voltage	240 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	210
Number of luminaires at LS C16A	210
Level of inrush current	12.8 A
Duration of inrush current	260 µs
Temperature at glass (light emission)	59 °C
Lumen	640 lm
Colour temperature	2700 Kelvin
Color	anthracite/brown

Light Source

916561		CRI	80
		Service life	50000 h
		Risk Group	1
		Width	9.85 cm
		Height	26 cm
		Depth	9.6 cm
		Net weight	1.2 kg
		Gross weight	1.4 kg