




HELIA PRO S | WL, up/down dali P1

HELIA PRO S, Wall-mounted light, up/down, DALI, P1, cylindrical, 2700 K, 6W, 24°, anthracite

The HELIA PRO S is a cylindrical surface-mounted wall luminaire designed for use in indoor and protected outdoor areas. It provides directed light distribution upwards and downwards and is equipped with DALI-2 dimming, allowing flexible light control. With a luminous flux of 600 lumens at 6 watts and a colour temperature of 2700 Kelvin, it ensures a pleasant, warm white illumination. The housing is made of aluminium and features an IP65 rating for protection against dust and water ingress, as well as an IK06 impact resistance class, ensuring a robust and durable construction. The luminaire includes an interchangeable reflector technology that allows adjustment of the light distribution to 10°, and it is supplied with a film for asymmetrical light distribution. With compact dimensions of 17.5 cm height, 6.5 cm diameter, and 10 cm depth, it is suitable for a variety of architectural applications.



Light source

2549480



Item no.	1010163
Lamps included	No
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	400 mA
Safety class	I
Wattage	6W
Minimum ambient temperature	-25°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Temperature at glass (light emission)	55
Beam angle	24°
Color	anthracite
CRI	80
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	17.5 cm

Accessories

1010939	Reflector S 10°, for THEO PRO and HELIA PRO
---------	---