




HELIA PRO L | WL, single dali P1

HELIA PRO L, Wall-mounted light, single, DALI, P1, cylindrical, 2700 K, 10W, 24°, white

The HELIA PRO L is a cylindrical surface-mounted wall luminaire suitable for use in indoor and outdoor areas where targeted lighting is required. It features DALI-2 dimming for flexible light control and delivers a luminous flux of 1200 lumens at 10 watts with a colour temperature of 2700 K. The light distribution can be adjusted using an interchangeable reflector with a 10° beam angle as well as a film for asymmetrical light distribution. The housing is made of aluminium and is designed for demanding environments with an IP65 protection rating and IK08 impact resistance. With a product depth of 15.5 cm, a diameter of 10.8 cm, and a height of 30.5 cm, the luminaire offers a compact design. The uniform dimensions and luminous fluxes enable optimal façade design.



Accessories

1010940	Reflector L 10°, for THEO PRO and HELIA PRO
---------	---

Item no.	1010170
Lamps included	No
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-25°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Temperature at glass (light emission)	55
Beam angle	24°
Color	white
CRI	80
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	30.5 cm