




HELIA PRO L | WL, up/down dali P1

HELIA PRO L, Wall-mounted light, up/down, DALI, P1, 2700 K, 20W, Touch, 24°, anthracite

The HELIA PRO L is a cylindrical surface-mounted wall luminaire designed for use in indoor and protected outdoor areas. It produces a directed light distribution with a beam angle of 24° and allows an adjustable light spread of 10° through an interchangeable reflector. The luminaire features a colour temperature of 2700 K and a luminous flux of 2400 lumens at a power consumption of 20 watts. The housing is made of aluminium and is equipped with a touch-sensitive DALI-2 dimming module, enabling flexible light control. The IP65 protection rating and IK08 impact resistance ensure a robust and durable design. The dimensions are 30.5 cm in height, 10.8 cm in diameter, and 15.5 cm in depth. The luminaire comes with a film for asymmetrical light distribution and offers a uniform façade design through consistent dimensions and luminous flux across different variants.



Accessories

1010940	Reflector L 10°, for THEO PRO and HELIA PRO
---------	---

Item no.	1010171
Lamps included	No
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	40
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	40.0
Number of luminaires at LS C16A	60.0
Level of inrush current	30 A
Duration of inrush current	100 µs
Temperature at glass (light emission)	55
Beam angle	24°
Color	anthracite
CRI	80
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	30.5 cm