




## HELIA PRO L | WL, single dali P2

**HELIA PRO L, Wall-mounted light, single, DALI, P2, cylindrical, 2700 K, 15W, 24°, white**

The HELIA PRO L is a cylindrical surface-mounted wall light suitable for use in indoor and outdoor areas where a robust and precise lighting solution is required. It features DALI-2 dimming and delivers a luminous flux of 1800 lumens at a power consumption of 15 watts with a warm white colour temperature of 2700 K. The luminaire is equipped with an interchangeable reflector for an adjustable beam angle of 10° and includes a film for asymmetrical light distribution. The housing is made of aluminium, the IP65 rating ensures protection against dust and jet water, and the impact resistance corresponds to IK08. With a height of 30.5 cm, a diameter of 10.8 cm, and a depth of 15.5 cm, the luminaire is compactly designed, allowing for a uniform façade design. The declared lifespan is 50,000 hours.



### Accessories

|         |                                             |
|---------|---------------------------------------------|
| 1010940 | Reflector L 10°, for THEO PRO and HELIA PRO |
|---------|---------------------------------------------|

|                                       |                    |
|---------------------------------------|--------------------|
| Item no.                              | 1010174            |
| Lamps included                        | No                 |
| Number of different light outlets     | 1                  |
| IP Code                               | IP65               |
| Impact resistance class               | IK08               |
| Impact resistance                     | 5 Joule            |
| Assembly                              | Surface            |
| Assembly details                      | Wall,              |
| Dimmable                              | true               |
| Dimming technology                    | DALI 2             |
| Number of through-wires               | 15                 |
| Primary nominal voltage               | 220-240V ~ 50/60Hz |
| Secondary power / voltage             | 380 mA             |
| Safety class                          | I                  |
| Wattage                               | 15 W               |
| Ambient temperature                   | 80                 |
| Minimum ambient temperature           | -25°C              |
| Maximum ambient temperature           | 45°C               |
| Number of luminaires at LS B16A       | 15.0               |
| Number of luminaires at LS C16A       | 24.0               |
| Level of inrush current               | 65 A               |
| Duration of inrush current            | 200 µs             |
| Temperature at glass (light emission) | 55                 |
| Beam angle                            | 24°                |
| Color                                 | white              |
| CRI                                   | 80                 |
| LXXBXX data                           | L80B10             |
| Service life                          | 50 000 h           |
| Risk Group                            | 1                  |