




HELIA PRO L | WL, up/down dali P2

HELIA PRO L, Wall-mounted light, up/down, DALI, P2, 2700 K, 30W, Touch, 24°, anthracite

The HELIA PRO L is a cylindrical surface-mounted wall luminaire designed for use in indoor and protected outdoor areas. It provides an up/down light distribution and is equipped with DALI-2 and touch dimming functions, allowing flexible light control. The luminaire delivers a luminous flux of 3600 lumens at a colour temperature of 2700 K with a beam angle of 24°. The housing is made of aluminium and features an IP65 protection rating as well as an IK08 impact resistance class, offering protection against dust, jet water, and mechanical impacts. The light distribution can be adjusted using a changeable reflector with a 10° beam, including a film for asymmetrical light distribution. Its compact dimensions and uniform luminous flux design facilitate integration into various façade and interior designs.



Accessories

1010940	Reflector L 10°, for THEO PRO and HELIA PRO
---------	---

Item no.	1010175
Lamps included	No
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	28
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	800 mA
Safety class	I
Wattage	30 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	28.0
Number of luminaires at LS C16A	42.0
Level of inrush current	30 A
Duration of inrush current	100 µs
Temperature at glass (light emission)	60
Beam angle	24°
Color	anthracite
CRI	80
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1