




HELIA PRO L | WL, up/down dali P2

HELIA PRO L, Wall-mounted light, up/down, DALI, P2, 2700 K, 30W, Touch, 24°, white

The HELIA PRO L is a cylindrical surface-mounted wall light suitable for use in indoor and protected outdoor areas. It features DALI-2 and touch dimming functions for flexible light control. With a luminous flux of 3600 lumens at 30 watts and a colour temperature of 2700 K, it provides pleasant light distribution, which can be adjusted to 10° using an interchangeable reflector. The housing is made of aluminium and is rated IP65 and IK08, ensuring high resistance to dust, water, and mechanical impacts. The luminaire measures 30.5 cm in height, 10.8 cm in diameter, and 15.5 cm in depth. It includes a film for asymmetrical light distribution and allows for uniform façade design through consistent dimensions and luminous flux values in both up and up/down versions.



Accessories

1010940	Reflector L 10°, for THEO PRO and HELIA PRO
---------	---

Item no.	1010176
Lamps included	No
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	28
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	800 mA
Safety class	I
Wattage	30 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	28.0
Number of luminaires at LS C16A	42.0
Level of inrush current	30 A
Duration of inrush current	100 µs
Temperature at glass (light emission)	60
Beam angle	24°
Color	white
CRI	80
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1