



## THEO PRO S

Wall-mounted light, single, DALI, P1, rectangular, 2700 K, 3W, 24°, anthracite

The THEO PRO wall light series combines a clear, square design with modern technology for precise accent lighting. Available in two sizes and performance classes, with single or up/down light, they offer versatile solutions for modern façade lighting in outdoor areas thanks to DALI control and resistance to sea air.

### TECHNICAL DATA

|                                   |                    |
|-----------------------------------|--------------------|
| Item no.                          | 1010177            |
| Number of different light outlets | 1                  |
| IP Code                           | IP65               |
| Impact resistance class           | IK 06              |
| Impact resistance                 | 1 Joule            |
| Assembly                          | Surface            |
| Assembly details                  | Wall               |
| Dimmable                          | Yes                |
| Dimming technology                | DALI 2             |
| Number of through-wires           | 15                 |
| Primary nominal voltage           | 220-240V ~50/60 Hz |
| Secondary power / voltage         | 350 mA             |
| Safety class                      | I                  |
| Wattage                           | 3 W                |
| Minimum ambient temperature       | -25 °C             |
| Maximum ambient temperature       | 45 °C              |
| Number of luminaires at LS B16A   | 15                 |
| Number of luminaires at LS C16A   | 24                 |
| Level of inrush current           | 65 A               |
| Duration of inrush current        | 200 µs             |
| Lumen                             | 300 lm             |
| Colour temperature                | 2700 Kelvin        |

## Light Source

|  |                                                                                   |
|--|-----------------------------------------------------------------------------------|
|  |  |
|--|-----------------------------------------------------------------------------------|

|              |            |
|--------------|------------|
| Beam angle   | 24 °       |
| Color        | anthracite |
| CRI          | 80         |
| Service life | 50000 h    |
| Risk Group   | 1          |
| Width        | 6.5 cm     |
| Height       | 17.5 cm    |
| Depth        | 10 cm      |
| Net weight   | 0.82 kg    |
| Gross weight | 1.03 kg    |