




## THEO PRO S

Wall-mounted light, single, DALI, P2, rectangular, 2700 K, 6W, 24°, anthracite

The THEO PRO wall light series combines a clear, square design with modern technology for precise accent lighting. Available in two sizes and performance classes, with single or up/down light, they offer versatile solutions for modern façade lighting in outdoor areas thanks to DALI control and resistance to sea air.



## TECHNICAL DATA

|                                       |                    |
|---------------------------------------|--------------------|
| Item no.                              | 1010181            |
| Number of different light outlets     | 1                  |
| IP Code                               | IP65               |
| Impact resistance class               | IK 06              |
| Impact resistance                     | 1 Joule            |
| Assembly                              | Surface            |
| Assembly details                      | Wall               |
| Dimmable                              | Yes                |
| Dimming technology                    | DALI               |
| Number of through-wires               | 15                 |
| Primary nominal voltage               | 220-240V ~50/60 Hz |
| Secondary power / voltage             | 150 mA             |
| Safety class                          | I                  |
| Wattage                               | 6 W                |
| Minimum ambient temperature           | -25 °C             |
| Maximum ambient temperature           | 45 °C              |
| Number of luminaires at LS B16A       | 15                 |
| Number of luminaires at LS C16A       | 24                 |
| Level of inrush current               | 65 A               |
| Duration of inrush current            | 200 µs             |
| Temperature at glass (light emission) | 56 °C              |
| Lumen                                 | 600 lm             |

## Light Source

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 1028936 |  |
|---------|-----------------------------------------------------------------------------------|

## Accessories

|         |  |
|---------|--|
| 1010939 |  |
|---------|--|

|                    |             |
|--------------------|-------------|
| Colour temperature | 2700 Kelvin |
| Beam angle         | 24 °        |
| Color              | anthracite  |
| CRI                | 80          |
| Service life       | 50000 h     |
| Risk Group         | 1           |
| Width              | 6.5 cm      |
| Height             | 17.5 cm     |
| Depth              | 10 cm       |
| Net weight         | 0.82 kg     |
| Gross weight       | 1.03 kg     |
| BIG WHITE Page     | 869         |