



THEO PRO L

Wall-mounted light, up/down, DALI, P1, 2700 K, 20W, Touch, 24°, anthracite

The THEO PRO wall light series combines a clear, square design with modern technology for precise accent lighting. Available in two sizes and performance classes, with single or up/down light, they offer versatile solutions for modern façade lighting in outdoor areas thanks to DALI control and resistance to sea air.

TECHNICAL DATA

Item no.	1010187
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	DALI,Touch
Number of through-wires	40
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	40
Number of luminaires at LS C16A	60
Level of inrush current	30 A
Duration of inrush current	100 µs
Temperature at glass (light emission)	35 °C
Lumen	2400 lm

Light Source

	
--	---

Accessories

1010940	
---------	--

Colour temperature	2700 Kelvin
Beam angle	24 °
Color	anthracite
CRI	80
Service life	50000 h
Risk Group	1
Width	10.8 cm
Height	30.5 cm
Depth	15.5 cm
Net weight	2.25 kg
Gross weight	2.85 kg
BIG WHITE Page	870