


MOTUNA | PD, PHASE

MOTUNA, PD, PHASE, pendant luminaire, 2700 K, 10 W, 130°, black / gold-colored

The MOTUNA pendant light is designed for indoor use and is particularly suitable for residential and commercial spaces. It features a round shape with a diameter of 38 cm and a height of just under 5 cm. The luminaire is made of aluminium and is mounted on a pendant suspension up to 250 cm long. With a luminous flux of 750 lumens, it provides efficient illumination. Dimming is achieved via trailing edge phase-cut control. The IP20 protection rating makes it suitable for dust-free, dry environments. The luminaire has a declared service life of 50,000 hours.



Item no.	1010216
Lamps included	No
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	113.0
Number of luminaires at LS C16A	181.0
Level of inrush current	8.5 A
Duration of inrush current	40 µs
Beam angle	130°
Color	black/gold
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	1
Height	5 cm
Diameter	38 cm
Pendant length	250.0000 cm
Net weight	1.73 kg
Gross weight	3.8 kg
BIG WHITE Page	197