


MOTUNA | CW, PHASE

MOTUNA, CW, PHASE, wall and ceiling surface-mounted luminaire, round, 2700 K, 10 W, 130°, black / gold-colored

The MOTUNA wall and ceiling surface-mounted luminaire is a ROUND fixture with a diameter of 38 cm and a height of 4.97 cm. It is suitable for mounting on walls and ceilings in indoor areas. The luminaire features PHASE-cut dimming and delivers a luminous flux of 750 lumens at a colour temperature of 2700 K. The housing is made of aluminium and is available in black and gold finishes. With a beam angle of 130°, it ensures uniform illumination. The IP20 protection rating indicates that the luminaire is designed for dry indoor environments. The declared service life is 50,000 hours.



Item no.	1010217
Lamps included	No
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250 mA
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	35°C
Number of luminaires at LS B16A	113.0
Number of luminaires at LS C16A	181.0
Level of inrush current	8.5 A
Duration of inrush current	40 µs
Beam angle	130°
Color	black/gold
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	1
Height	5 cm
Diameter	38 cm
Net weight	1.27 kg
Gross weight	2.8 kg
BIG WHITE Page	163