


MOTUNA | PD, PHASE

MOTUNA, PD, PHASE, pendant luminaire, 2700 K, 10 W, 130°, white / gold-colored

The MOTUNA pendant light is designed for indoor use and is particularly suitable for applications in residential and commercial spaces. It features a round shape with a diameter of 38 cm and a height of 4.97 cm. The luminaire is made of aluminium and is mounted on a pendant length of 250 cm. With a light output of 1000 lumens, it provides efficient illumination. Dimming is achieved via phase-cut control, allowing flexible light adjustment. The IP20 rating indicates protection against contact and solid foreign objects, but not against moisture. The declared LED lifespan is 50,000 hours.



Item no.	1010366
Lamps included	No
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/50Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	113.0
Number of luminaires at LS C16A	181.0
Level of inrush current	8.5 A
Duration of inrush current	40 µs
Beam angle	130°
Color	white/gold
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	1
Height	5 cm
Diameter	38 cm
Pendant length	250.0000 cm
Net weight	1.73 kg
Gross weight	3.8 kg
BIG WHITE Page	197