

## DOWNLIGHT VARIO 220 22 830/840 WH ML PIR

DOWNLIGHT VARIA is your all-round lighting solution. A round, minimalist design. Available in two diameters: 22 cm and 29 cm. Easy to install. Equipped with a CCT switch, you can select your ideal colour temperature (3000 K and 4000 K). The wattage control allows you to easily adjust the light intensity - up to 3000 lumens for the 29cm version. There are also two models: on/off and with PIR sensor.

### TECHNICAL DATA

|                                   |                              |
|-----------------------------------|------------------------------|
| Item no.                          | 1010399                      |
| Number of different light outlets | 1                            |
| IP Code                           | IP20                         |
| Impact resistance class           | IK 03                        |
| Assembly                          | Recessed                     |
| Assembly details                  | Ceiling                      |
| Number of through-wires           | 30                           |
| Primary nominal voltage           | 220-240V ~50/60 Hz           |
| Secondary power / voltage         | 90/180 mA                    |
| Safety class                      | II                           |
| Wattage                           | 9 W                          |
| Maximum ambient temperature       | 40 °C                        |
| Number of luminaires at LS B16A   | 80                           |
| Number of luminaires at LS C16A   | 80                           |
| Level of inrush current           | 6.34 A                       |
| Duration of inrush current        | 38.8 µs                      |
| Lumen                             | 1150 / 1200 / 2200 / 2250 lm |
| Colour temperature                | 3000/4000/3000/4000 Kelvin   |
| Beam angle                        | 110 °                        |
| Color                             | white                        |
| CRI                               | 80                           |
| UGR ≤                             | 28                           |

## Light Source

|  |                                                                                   |
|--|-----------------------------------------------------------------------------------|
|  |  |
|--|-----------------------------------------------------------------------------------|

|                       |         |
|-----------------------|---------|
| Service life          | 50000 h |
| Risk Group            | 1       |
| Height                | 2.2 cm  |
| Diameter              | 22.7 cm |
| Net weight            | 0.47 kg |
| Gross weight          | 0.63 kg |
| Shape of cut-out      | TBD     |
| Installation depth    | 3 cm    |
| Installation diameter | 19.5 cm |