

## PANEL 60

pendant light, round, DALI, pendant length 200 cm, 3000/4000K, 90°, grey

The new PANEL 60 - the efficient lighting solution for office and general areas. With a switchable colour temperature (3,000/4,000 K), CRI>90, improved energy efficiency and UGR<19, it meets all the requirements of modern workplaces. Ideal as a replacement for existing systems: simply replace and benefit immediately!

## TECHNICAL DATA

|                                   |                    |
|-----------------------------------|--------------------|
| Item no.                          | 1010429            |
| Number of different light outlets | 1                  |
| IP Code                           | IP20               |
| Impact resistance class           | IK 02              |
| Impact resistance                 | 0.2 Joule          |
| Assembly                          | Surface            |
| Dimmable                          | Yes                |
| Dimming technology                | DALI,Touch         |
| Primary nominal voltage           | 220-240V ~50/60 Hz |
| Secondary power / voltage         | 750 mA             |
| Safety class                      | I                  |
| Wattage                           | 29 W               |
| Maximum ambient temperature       | 45 °C              |
| Number of luminaires at LS B16A   | 29                 |
| Number of luminaires at LS C16A   | 48                 |
| Level of inrush current           | 14.75 A            |
| Duration of inrush current        | 256 µs             |
| Lumen                             | 3050 / 3300 lm     |
| Colour temperature                | 3000/4000 Kelvin   |
| Beam angle                        | 90 °               |
| Color                             | gray               |
| CRI                               | 90                 |

## Light Source

|  |                                                                                   |
|--|-----------------------------------------------------------------------------------|
|  |  |
|--|-----------------------------------------------------------------------------------|

|                |         |
|----------------|---------|
| UGR ≤          | 19      |
| Service life   | 50000 h |
| Risk Group     | 1       |
| Height         | 1.2 cm  |
| Diameter       | 60 cm   |
| Pendant length | 200 cm  |
| Net weight     | 4.25 kg |
| Gross weight   | 5.83 kg |