


P-LIGHT

wall and ceiling-mounted light, rectangular, 6000K, 3W, white / transparent

P-LIGHT - reliable emergency and safety lighting for escape and rescue routes. With a 3-hour emergency operating time, self-test function, modern rechargeable battery technology and a 5-year guarantee, the lights ensure maximum safety. Pictogram sets and mounting sets are included in the scope of delivery - for fast, standard-compliant installation.



TECHNICAL DATA

Item no.	1010504
Number of different light outlets	1
Horizontal rotation range	90 °
IP Code	IP20
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ceiling, Wall
Primary nominal voltage	220-240V ~50/60 Hz
Safety class	II
Wattage	3 W
Minimum ambient temperature	0 °C
Maximum ambient temperature	45 °C
Lumen	37 lm
Colour temperature	6000 Kelvin
Color	white/transparent
CRI	80
Service life	50000 h
Length	30.5 cm
Width	3.5 cm
Height	23 cm
Net weight	0.8 kg

Gross weight	0.94 kg
--------------	---------

Accessories

1010497	P-LIGHT , set of 6, pictogram foil, B: 15.5 H: 30 cm, green
1010495	P-LIGHT , installation kit for P-LIGHT 3W
1010496	P-LIGHT , wall mounting set for P-LIGHT
1010927	P-LIGHT , suspension set