


GLENOS® PRO

pendant light, 1.5m, DALI, UGR16, pendant length 210 cm, 4000K, 75°, white / black

GLENOS® PRO is the new linear light range from SLV for sophisticated office and contract lighting. Whether pendant, surface mounted or recessed, all lights are glare-free (UGR<16/19) thanks to the micro-reflector and offer high efficiency of up to 134 lm/W with CRI>90. The lights can be connected seamlessly without light spillage, are halogen-free and guarantee uniform illumination with high visual comfort.



TECHNICAL DATA

Item no.	1010515
Number of different light outlets	2
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Dimmable	Yes
Dimming technology	DALI, Touch
Number of through-wires	13
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	1850 mA
Safety class	I
Wattage	70 W
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	10
Number of luminaires at LS C16A	17
Level of inrush current	30 A
Duration of inrush current	346 µs
Lumen	9400 lm
Colour temperature	4000 Kelvin
Beam angle	75 °
Color	white/black

Light Source

CRI	90
UGR ≤	16
Service life	50000 h
Risk Group	1
Length	144.8 cm
Width	4.8 cm
Height	7.6 cm
Pendant length	210 cm
Net weight	3.8 kg
Gross weight	5.6 kg