


PAVANNO625 45 830/840/850 BK WH UGR24

PAVANNO: energy-efficient, durable, eligible for subsidies. With up to 190 lm/W, 100,000 h service life, UGR<19, multi-lumen/colour and DALI control, the luminaire is perfect for working environments such as offices, training rooms or healthcare facilities.



TECHNICAL DATA

| | |
|---------------------------------|-----------------------|
| Item no. | 1010578 |
| IP Code | IP20 |
| Impact resistance class | IK 02 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~0/50/60 Hz |
| Secondary power / voltage | 500-1100 mA |
| Safety class | II |
| Wattage | 17 W |
| Ambient temperature | 80 °C |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Number of luminaires at LS B16A | 27 |
| Number of luminaires at LS C16A | 45 |
| Level of inrush current | 19.1 A |
| Duration of inrush current | 220 µs |
| Lumen | 2809 / 6538 lm |
| Colour temperature | 3000/4000/5000 Kelvin |
| Beam angle | 80 ° |
| Color | black |
| CRI | 80 |
| UGR ≤ | 19 |

| | |
|---------------------|----------|
| Service life | 100000 h |
| Risk Group | 1 |
| Length | 62 cm |
| Width | 62 cm |
| Height | 2 cm |
| Net weight | 3.2 kg |
| Gross weight | 3.4 kg |