




TRACKSPOT P 3PH. 34 940 | P90 3PH. 34 940 MB ML BK

TRACKSPOT, P90 3PH. 34 940 MB ML BK

The TRACKSPOT P is a 3~ spot lighting module designed for mounting on ceiling or wall track systems. Typical applications are indoor areas where targeted lighting is required. The luminaire features a cylindrical design and is made from an aluminium housing. With a length of 17.3 cm, a diameter of 9 cm, and a height of 14 cm, it is compactly sized. The light output ranges from 2940 to 3890 lumens with a beam angle of 36 degrees. The IP20 protection rating and impact resistance of IK03 provide standard protection against contact and mechanical impacts. The luminaire is designed for use on three-phase track systems and offers a declared service life of 50,000 hours.



Light source

2194037



Item no.	1010593
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK03
Assembly	Track
Assembly details	Ceiling, Wall,
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	450-600mA
Safety class	II
Wattage	17 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	36°
Color	black
CRI	90
UGR ≤	25
LXXBXX data	L80B10
Service life	50 000 h
Length	17.3 cm
Height	14 cm
Diameter	9 cm
Net weight	0.81 kg
Gross weight	0.95 kg