




TRACKSPOT P 3PH. 33 930 | P90 3PH. 33 930 WB ML WH

TRACKSPOT, P90 3PH. 33 930 MB ML WH

The TRACKSPOT P is a three-PHASE spotlight designed for mounting on ceiling and wall track systems. It is particularly suitable for indoor use where targeted lighting is required. The light source delivers a luminous flux between 2850 and 3720 lumens, enabling bright illumination. The housing is made of aluminium and has a cylindrical shape, with compact dimensions of 17.3 cm in length, 9 cm in diameter, and 14 cm in height. The spotlight features an IP20 protection rating and an impact resistance class of IK03. The light distribution is defined by a 47° beam angle. The declared service life is 50,000 hours, ensuring long-lasting operation.



Light source

2194030



Item no.	1010600
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK03
Assembly	Track
Assembly details	Ceiling, Wall,
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	450-600mA
Safety class	II
Wattage	17 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	47°
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L80B10
Service life	50 000 h
Length	17.3 cm
Height	14 cm
Diameter	9 cm
Net weight	0.81 kg
Gross weight	0.95 kg