


PANEL P

595 45 830 WB UGR19 DALI

PANEL P is the ideal choice for refurbishments and new builds: 100,000 h service life, up to 200 lm/W, UGR<19, DALI options, emergency lighting capability and multi-lumen via DIP switch. Through-wiring included - for an efficient, future-proof lighting solution in the property sector.



TECHNICAL DATA

Item no.	1010750
IP Code	IP20
Impact resistance class	IK 02
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	600-950 mA
Safety class	II
Wattage	26 W
Ambient temperature	80 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	29
Number of luminaires at LS C16A	48
Level of inrush current	14.75 A
Duration of inrush current	256 µs
Lumen	4179 / 6464 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	white
CRI	80
Binning	3 SDCM

Light Source

2385579	
---------	---

Accessories

1007474	PANEL 600 , assembly mounting frame
1007575	PANEL 600 , recessed mounting frame

Service life	100000 h
Length	59.5 cm
Width	59.5 cm
Height	3.6 cm
Net weight	1.9 kg
Gross weight	2.1 kg