


DOWNLIGHT P

84 12 WM 840 60 ML WH IP54

The DOWNLIGHT P combines a robust design with high efficiency: up to 170 lm/W, 80,000 h service life (L80B10) and multi-lumen function make it the ideal choice for offices, corridors or common areas. With a UGR value of 21 or 23, it provides pleasant light - available in versions with DALI control or as an on/off version.



TECHNICAL DATA

Item no.	1010757
IP Code	IP54
Impact resistance class	IK 08
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	100-200 mA
Safety class	II
Wattage	5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	36
Number of luminaires at LS C16A	60
Level of inrush current	7.9 A
Duration of inrush current	2.6 µs
Lumen	550 / 1090 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	80
Binning	3 SDCM
Service life	50000 h
Depth	5.7 cm
Diameter	8.6 cm

Light Source

2194011	
---------	---

Net weight	0.35 kg
Gross weight	0.43 kg
Shape of cut-out	round
Installation diameter	6.8 cm