


DOWNLIGHT P

230 40 HG 840 60 ML WH IP54

The DOWNLIGHT P combines a robust design with high efficiency: up to 170 lm/W, 80,000 h service life (L80B10) and multi-lumen function make it the ideal choice for offices, corridors or common areas. With a UGR value of 21 or 23, it provides pleasant light - available in versions with DALI control or as an on/off version.



TECHNICAL DATA

Item no.	1010769
IP Code	IP54
Impact resistance class	IK 08
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	600-750 mA
Safety class	II
Wattage	22 W
Ambient temperature	85 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	36
Number of luminaires at LS C16A	60
Level of inrush current	21 A
Duration of inrush current	180 µs
Lumen	4030 / 5150 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	80
Binning	3 SDCM
Service life	50000 h
Depth	9.5 cm

Light Source

2194011		Diameter	23 cm
		Net weight	1.14 kg
		Gross weight	1.31 kg
		Shape of cut-out	round
		Installation diameter	20 cm