



WATERPROOF P

1500 81 830/840/850 ML IP66

The WATERPROOF moisture-proof luminaire offers energy-efficient lighting solutions in three performance classes, with up to 180 lm/W, IP66, IK08 and a service life of up to 100,000 hours. Thanks to tool-free cap opening and integrated through-wiring, installation is particularly quick. Optionally with DALI and sensor - ideal for industry, warehouses or underground car parks.



TECHNICAL DATA

Item no.	1010825
IP Code	IP66
Impact resistance class	IK 08
Assembly	Surface
Assembly details	Ceiling, Wall
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	200-350 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	18
Number of luminaires at LS C16A	31
Level of inrush current	33.1 A
Duration of inrush current	168 µs
Lumen	4434 / 8123 lm
Colour temperature	3000/4000/5000 Kelvin
Beam angle	120 °
Color	gray
UGR ≤	27
Service life	100000 h
Risk Group	1

Light Source

2481888	
---------	---

Length	150 cm
Width	8 cm
Height	7.4 cm
Net weight	1.76 kg
Gross weight	1.98 kg