




BATTEN FLAT P

600 27 830/840/850 ML WH

BATTEN FLAT P - the robust IP44 solution for multi-storey car parks, corridors/hallways or plant rooms. The multi-lumen and multi-CCT function (3,000/4,000/5,000 K) allows the light output to be flexibly adjusted. Variants with DALI2 control or integrated HF motion sensor automatically activate the light only when there is movement, thus enabling energy-saving, intelligent operation. The end caps, which can be opened without tools, simplify maintenance and installation.



TECHNICAL DATA

Item no.	1010907
IP Code	IP44
Impact resistance class	IK 04
Impact resistance	0.5 Joule
Assembly	Surface
Assembly details	Ceiling, Wall
Number of through-wires	128
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	200-350 mA
Safety class	I
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	57
Number of luminaires at LS C16A	96
Level of inrush current	9.7 A
Duration of inrush current	205 µs
Lumen	1619 / 2837 lm
Colour temperature	3000/4000/5000 Kelvin
Beam angle	120 °
Color	white
CRI	80

Light Source

2481883	
	

Accessories

1010932	BATTEN FLAT P , Suspension kits with 2m 2pcs
1010934	BATTEN FLAT P Micro-wave sensor , on off, max 5m
1010931	BATTEN FLAT P , Wall brackets, 2pcs
1010933	BATTEN FLAT P , Horizontal cable wire suspension kits, 2pcs

UGR ≤	25
Service life	100000 h
Risk Group	1
Length	64.6 cm
Width	15.2 cm
Height	5.2 cm
Net weight	1.8 kg
Gross weight	2.03 kg