




DOWNLIGHT P

165 30 WM 830 60 ML WH IP54

Discreet and universal: the UNIVERSAL DOWNLIGHT PHASE recessed light creates targeted lighting thanks to its narrow beam angle of 38 degrees. The IP65 protection class rating means it is protected against dirt and even jets of water. The colour temperature (2700/3000/4000/6500 K) can be selected via the CCT switch before installation. Natural colour reproduction is achieved with a CRI of over 90. And the Quick Connector Box ensures the downlight is quick and easy to install. You can also use the separately available decorative ring, which comes in white, black, gold or chrome.



TECHNICAL DATA

Item no.	1011300
IP Code	IP20/IP54
Impact resistance class	IK 08
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500-650 mA
Safety class	II
Wattage	19 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	36
Number of luminaires at LS C16A	60
Level of inrush current	7.9 A
Duration of inrush current	2.6 µs
Lumen	1950 / 3960 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	80
Depth	8.2 cm
Diameter	16.5 cm
Net weight	0.76 kg
Gross weight	0.87 kg

Light Source

2545097

