




## TUBULAR P 1200 500 850 | WH DALI2 OPL PC

### TUBULAR P, 1200 500 850 WH DALI2 OPL PC

The TUBULAR P series is a robust LED lighting solution for demanding industrial and wet room applications. With protection ratings up to IP69K and HACCP-compliant design, it is suitable for hygienically sensitive areas and for use in high-pressure cleaning and at elevated temperatures. The version with an opal or clear cover enables defined light distribution depending on the application. The integrated DALI-2 interface allows connection to standardised lighting control systems.



|  |                      |
|--|----------------------|
|  | 1011525              |
|  | IP66/IP69K           |
|  | IK10                 |
|  | true                 |
|  | DALI,                |
|  | 220-240V ~0/50/60 Hz |
|  | 300 mA               |
|  | I                    |
|  | 35 W                 |
|  | 80                   |
|  | -20°C                |
|  | 40°C                 |
|  | 30.0                 |
|  | 49.0                 |
|  | 17 A                 |
|  | 222 µs               |
|  | 120°                 |
|  | 80                   |
|  | 27                   |
|  | L80B10               |
|  | 100 000 h            |
|  | 1                    |
|  | 115 cm               |
|  | 7.5 cm               |
|  | 1.51 kg              |
|  | 1.55 kg              |