
MEDO 2 SLIM 30 | CL, PHASE

MEDO 2 SLIM 30, CL, PHASE, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 8 W, 85°, white

The MEDO 2 SLIM 30 is a surface-mounted ceiling light suitable for general indoor lighting. It features a colour temperature of 3000/4000 K and a power consumption of 8 watts with a beam angle of 85°. The housing is made of aluminium and steel, measuring 29.5 cm in diameter and 4.9 cm in height. The luminaire is equipped with phase-cut dimming, allowing flexible light control. With an IP20 rating, it is designed for use in dry indoor environments. The impact resistance corresponds to IK03 class. This luminaire is suitable for use in residential and commercial spaces where efficient and dimmable ceiling lighting is required.



Item no.	1011694
IP Code	IP20
Impact resistance class	IK03
Assembly	Surface
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200 mA
Safety class	I
Wattage	8 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	56.0
Number of luminaires at LS C16A	118.0
Level of inrush current	5 A
Duration of inrush current	300 µs
Beam angle	85°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	0
Height	4.9 cm
Diameter	29.5 cm
Net weight	2.1 kg
Gross weight	3.1 kg
BIG WHITE Page	198

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white