
MEDO 2 SLIM 60 | CL, PHASE

MEDO 2 SLIM 60, CL, PHASE, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 35 W, 85°, white

The MEDO 2 SLIM 60 is a surface-mounted ceiling luminaire designed for indoor use. It delivers a luminous flux of 4200 lumens with a power consumption of 35 watts and is available with a colour temperature of 3000 or 4000 Kelvin and a beam angle of 85 degrees. The luminaire features PHASE-cut dimming, allowing for stepless brightness adjustment. Its housing is made of aluminium and steel, has a slim design, and measures 58.7 cm in diameter and 4.8 cm in height. The luminaire has an IP20 rating and an impact resistance of IK03. These characteristics make it suitable for use in commercial and public indoor spaces where uniform and dimmable general lighting is required.



Item no.	1011698
IP Code	IP20
Impact resistance class	IK03
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	30
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	35 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	72.0
Number of luminaires at LS C16A	72.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	85°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	0
Height	4.8 cm
Diameter	58.7 cm
Net weight	5.8 kg
Gross weight	7.5 kg
BIG WHITE Page	199

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white