
MEDO 2 SLIM 80 | CL, PHASE

MEDO 2 SLIM 40, CL, PHASE, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 45 W, 85°, white

The MEDO 2 SLIM 80 is a surface-mounted ceiling luminaire suitable for indoor use. It features a luminous flux of 5900 lumens at a power consumption of 45 watts and offers a colour temperature of 3000 or 4000 Kelvin with a beam angle of 85 degrees. The housing is made of aluminium and steel, with a diameter of 76.8 cm and a height of 4.8 cm. The luminaire is equipped with PHASE-cut dimming and has an IP20 protection rating as well as an impact resistance class of IK03. These technical specifications make the luminaire ideal for applications requiring a slim design and dimmable, high-performance lighting.



Item no.	1011700
IP Code	IP20
Impact resistance class	IK03
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	20
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	1200 mA
Safety class	I
Wattage	45 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	50.0
Number of luminaires at LS C16A	50.0
Level of inrush current	5 A
Duration of inrush current	300 µs
Beam angle	85°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	0
Height	4.8 cm
Diameter	76.8 cm
Net weight	9.5 kg
Gross weight	11 kg
BIG WHITE Page	199

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white