


MEDO 2 SLIM 60 | CL, DALI

MEDO 2 SLIM 60, CL, DALI, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 34 W, 85°, black

The MEDO 2 SLIM 60 is a surface-mounted ceiling luminaire suitable for indoor use. It provides a luminous flux of 4200 lumens with a colour temperature of 3000 or 4000 Kelvin and a beam angle of 85 degrees. The luminaire features DALI 2 and touch dimming, allowing flexible light control. The housing is made of aluminium and steel, measuring 58.7 cm in diameter and 4.8 cm in height. With an IP20 rating and IK03 impact resistance, it ensures reliable operation in protected environments. This luminaire is particularly suitable for applications requiring a slim design and precise light distribution.



Item no.	1011705
IP Code	IP20
Impact resistance class	IK03
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	30
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	34 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	25.0
Number of luminaires at LS C16A	42.0
Level of inrush current	27 A
Duration of inrush current	111 µs
Beam angle	85°
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	0
Height	4.8 cm
Diameter	58.7 cm
Net weight	5.8 kg
Gross weight	7.5 kg
BIG WHITE Page	201

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white