


MEDO 2 SLIM 80 | CL, DALI

MEDO 2 SLIM 80, CL, DALI, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 45 W, 85°, black

The MEDO 2 SLIM 80 is a surface-mounted ceiling luminaire designed for indoor use. It offers a luminous flux of 5900 lumens with selectable colour temperatures of 3000 and 4000 Kelvin and a beam angle of 85 degrees. The luminaire features DALI-2 dimming and touch control, allowing flexible light adjustment. The housing is made of aluminium and steel, with a diameter of 76.8 cm and a height of 4.8 cm. Protection class IP20 and impact resistance to IK03 ensure reliable operation in protected environments. The MEDO 2 SLIM 80 is designed for professional applications requiring efficient and controllable ceiling lighting.



Item no.	1011707
IP Code	IP20
Impact resistance class	IK03
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	20
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	1200 mA
Safety class	I
Wattage	45 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	16.0
Number of luminaires at LS C16A	26.0
Level of inrush current	26 A
Duration of inrush current	264 µs
Beam angle	85°
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	0
Height	4.8 cm
Diameter	76.8 cm
Net weight	9.5 kg
Gross weight	11 kg
BIG WHITE Page	201

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white