




ENOLA 2.0 M | 3PH., PD, SINGLE, GU10, QPAR51

ENOLA 2.0 M, 3~ pendant luminaire, SINGLE, QPAR51, 1 x 10 W, black

The ENOLA 2.0 M is a three-phase pendant luminaire typically used indoors for targeted lighting. It features a single light source with a GU10 socket and a power output of 10 watts. The housing is made of aluminium and polycarbonate, ensuring a robust and dimensionally stable construction. Designed as a track pendant, the luminaire has a suspension length of 200 centimetres, with a product diameter of 5.8 centimetres and a height of 10.5 centimetres. The IP20 protection rating and IK02 impact resistance provide protection against contact and minor mechanical impacts. The ENOLA 2.0 M is suitable for use in track systems and offers flexible mounting options for various lighting scenarios.



Item no.	1011715
Socket	GU10
Number of sockets	1
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Pendant mounted,
Primary nominal voltage	220-240V ~ 50/60Hz
Safety class	II
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Color	black
Height	10.5 cm
Diameter	5.8 cm
Pendant length	200.0000 cm
Net weight	0.25 kg
Gross weight	0.34 kg
BIG WHITE Page	565

Recommended light bulbs

1005077	LED lightbulb QPAR51, GU10, 2700 K, black
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Accessories

1011749	ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black
1011750	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white
1011751	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold
1011752	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper