


# ENOLA 2.0 M | 3PH., PD, SINGLE, GU10, QPAR51

**ENOLA 2.0 M, 3~ pendant luminaire, SINGLE, QPAR51, 1 x 10 W, white**

The ENOLA 2.0 M is a 3~ pendant luminaire suitable for indoor lighting. It is designed for track pendant mounting and features a suspension length of 200 centimetres. The housing is made of aluminium and polycarbonate, ensuring a robust construction. The luminaire is equipped with a QPAR51 socket for a 10-watt lamp. With a product diameter of 5.8 centimetres and a height of 10.5 centimetres, it offers a compact design. The protection rating is IP20, and the impact resistance corresponds to IK02 class. These characteristics make the ENOLA 2.0 M a functional solution for use in various indoor areas, where technical quality and easy integration are prioritised.




| | |
|---|---|
| **Item no.** | 1011716 |
| **Socket** | GU10 |
| **Number of sockets** | 1 |
| **IP Code** | IP20 |
| **Impact resistance class** | IK02 |
| **Assembly** | Track |
| **Assembly details** | Pendant mounted, |
| **Primary nominal voltage** | 220-240V ~ 50/60Hz |
| **Safety class** | II |
| **Wattage** | 10 W |
| **Minimum ambient temperature** | -20°C |
| **Maximum ambient temperature** | 40°C |
| **Color** | white |
| **Height** | 10.5 cm |
| **Diameter** | 5.8 cm |
| **Pendant length** | 200.0000 cm |
| **Net weight** | 0.25 kg |
| **Gross weight** | 0.34 kg |
| **BIG WHITE Page** | 565 |

## Recommended light bulbs

| | |
|---|---|
| **1005076** | LED lightbulb QPAR51, GU10, 2700 K, white |
| **1012469** | LED PAR16 Smart, GU10, Tunable White, Zigbee |

## Accessories

| | |
|---|---|
| **1011749** | ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black |
| **1011750** | ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white |
| **1011751** | ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold |
| **1011752** | ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper |