




ENOLA 2.0 M | 1PH., PD, SINGLE, GU10, QPAR51

ENOLA 2.0 M, 1~ pendant luminaire, SINGLE, QPAR51, 1 x 10 W, black

The 1~ pendant light ENOLA 2.0 M is designed for track system pendant mounting and is suitable for indoor use with an IP20 rating. The luminaire housing is made of aluminium, combined with a diffuser made of polycarbonate (PC). With a pendant length of 200 centimetres and compact dimensions of 5.8 cm in diameter and 10.5 cm in height, it offers a flexible and space-saving lighting solution. The luminaire is designed for GU10 sockets with QPAR51 lamps and features an impact resistance rating of IK02, ensuring moderate robustness. This pendant light is particularly suitable for use in residential and commercial spaces where targeted, track-based lighting is desired.



Item no.	1011717
Socket	GU10
Number of sockets	1
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Pendant mounted,
Primary nominal voltage	220-240V ~ 50/60Hz
Safety class	II
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Color	black
Height	10.5 cm
Diameter	5.8 cm
Pendant length	200.0000 cm
Net weight	0.24 kg
Gross weight	0.33 kg
BIG WHITE Page	501

Recommended light bulbs

1005077	LED lightbulb QPAR51, GU10, 2700 K, black
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Accessories

1011749	ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black
1011750	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white
1011751	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold
1011752	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper