




ENOLA 2.0 M | 1PH.,PD , SINGLE, GU10, QPAR51

ENOLA 2.0 M, 1~ Hanglamp, SINGLE, QPAR51, 1 x 10 W, zwart

The 1~ pendant luminaire ENOLA 2.0 M is designed for track pendant mounting and is suitable for indoor use with an IP20 protection rating. The luminaire housing is made of aluminum, combined with a diffuser made of polycarbonate (PC). With a pendant length of 200 centimeters and compact dimensions of 5.8 cm diameter and 10.5 cm height, it offers a flexible and space-saving lighting solution. The luminaire is designed for GU10 sockets with QPAR51 lamps and features an impact resistance class of IK02, ensuring moderate robustness. This pendant luminaire is particularly suitable for use in residential and commercial spaces where targeted, track-based lighting is desired.



Art.nr.	1011717
Fitting	GU10
Aantal fittingen	1
IP-code	IP20
Slagvastheidsklasse	IK02
Montage	Rail
Montagebeschrijving	Pendelmontage,
Primaire nominale spanning	220-240V V ~ 50/60Hz
Veiligheidsklasse	II
Wattage	10 W
minimale omgevingstemperatuur	-20°C
maximale omgevingstemperatuur	40°C
Kleur	zwart
Hoogte	10.5 cm
Diameter	5.8 cm
Pendellengte	200.0000 cm
Nettogewicht	0.24 kg
Brutogewicht	0.33 kg

Aanbevolen lampen

1005077	Led lichtbron QPAR51, GU10, 2700 K, zwart
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Accessoires

1011749	ENOLA 2.0/BIMA 2.0 M, decoratiering, Ø 54 mm, zwart
1011750	ENOLA 2.0/BIMA 2.0 M, decoratiering, Ø 54 mm, wit
1011751	ENOLA 2.0/BIMA 2.0 M, decoratiering, Ø 54 mm, goud
1011752	ENOLA 2.0/BIMA 2.0 M, decoratiering, Ø 54 mm, koper