


# ENOLA 2.0 S | 3PH., PD, SINGLE, GU10 MINI, PAR11

**ENOLA 2.0 M, 3~ pendant luminaire, SINGLE, GU10 MINI, PAR11, 1 x 5 W, white**

The ENOLA 2.0 M is a three-phase pendant luminaire with a single GU10 MINI PAR11 lamp, designed for a power of 5 watts. It is suitable for indoor lighting, for example in residential and commercial spaces. The housing is made of aluminium and polycarbonate, ensuring a stable and durable construction. With a pendant length of 200 centimetres and compact dimensions of 4.2 cm diameter and 9 cm height, the luminaire can be installed flexibly in various ceiling heights. The IP20 protection rating safeguards against contact and foreign objects, while the impact resistance corresponds to IK02 class. The luminaire is mounted as a track pendant, allowing easy integration into three-phase track systems.




| | |
|---|---|
| **Item no.** | 1011726 |
| **Socket** | GU10 |
| **Number of sockets** | 1 |
| **IP Code** | IP20 |
| **Impact resistance class** | IK02 |
| **Assembly** | Track |
| **Assembly details** | Pendant mounted, |
| **Primary nominal voltage** | 220-240V ~ 50/60Hz |
| **Safety class** | II |
| **Wattage** | 5 W |
| **Minimum ambient temperature** | -20°C |
| **Maximum ambient temperature** | 40°C |
| **Color** | white |
| **Height** | 9 cm |
| **Diameter** | 4.2 cm |
| **Pendant length** | 200.0000 cm |
| **Net weight** | 0.2 kg |
| **Gross weight** | 0.3 kg |
| **BIG WHITE Page** | 564 |

## Recommended light bulbs

| | |
|---|---|
| **1011670** | LED, PAR11 GU10, LED lamp, PHASE, 4.9 W, 2700 K, CRI 90, 36°, white |

## Accessories

| | |
|---|---|
| **1011753** | ENOLA 2.0 S, decorative ring, 39 mm, black |
| **1011754** | ENOLA 2.0 S, decorative ring, 39 mm, white |
| **1011755** | ENOLA 2.0 S, decorative ring, 39 mm, gold |
| **1011756** | ENOLA 2.0 S, decorative ring, 39 mm, copper |