


STREET A MINI 135 730 | LENS710

STREET A, MINI 135 730 LENS710

The STREET A MINI 135 730 is a streetlight designed for use in public lighting. It is particularly suitable for illuminating roads and pathways. The luminaire has a luminous flux of 13,500 lumens and a declared lifespan of 100,000 hours. The housing is made of aluminium, with a glass cover. With dimensions of 66.4 cm in length, 25.1 cm in width, and 13.2 cm in height, it is compactly constructed. The IP66 protection rating ensures high protection against dust and powerful jet water, while the IK09 impact resistance class provides protection against mechanical impacts. The STREET A MINI is designed as a luminaire head, meeting the requirements for robust and durable street lighting.



Item no.	1011732
Number of different light outlets	1
IP Code	IP66
Impact resistance class	IK09
Impact resistance	10 Joule
Primary nominal voltage	220-240V V ~ 50/60Hz
Secondary power / voltage	610 mA
Safety class	I
Wattage	90 W
Minimum ambient temperature	-40°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	10.0
Number of luminaires at LS C16A	17.0
Level of inrush current	41.6 A
Duration of inrush current	238 µs
Beam angle	160°
Color	gray
CRI	70
LXXBXX data	L80B50
Service life	100 000 h
Risk Group	1
Length	66.4 cm
Width	25.1 cm
Height	13.2 cm
Net weight	5.8 kg
Gross weight	6.1 kg