




WL 149 | WL, PHASE

WL 149, WL, PHASE, surface-mounted wall luminaire, 3000 K, 10 W, black

The WL 149 is a surface-mounted wall light suitable for indoor lighting. It features a colour temperature of 3000 K and delivers a luminous flux of 600 lumens with a power consumption of 10 watts. The luminaire is equipped with PHASE-cut dimming, allowing flexible brightness adjustment. The housing is made of steel and glass, ensuring a robust construction. With dimensions of 24 cm width, 6 cm height, and 10 cm depth, the light is compactly designed. The IP20 rating makes it suitable for use in dry indoor environments. The WL 149 offers a declared life-span of 50,000 hours and is designed for use in residential and work areas.



Light source

2014568



Item no.	1011747
IP Code	IP20
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	56.0
Number of luminaires at LS C16A	118.0
Level of inrush current	5 A
Duration of inrush current	300 µs
Color	black
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Width	24 cm
Height	6 cm
Depth	10
Net weight	1.11 kg
Gross weight	1.32 kg
BIG WHITE Page	347