




DORISA 30 | WL

DORISA 30, WL, Wall surface-mounted luminaire, 4000 K, 5.2 W, 110°, black

The DORISA 30 WL is a surface-mounted wall light suitable for use in indoor and protected outdoor areas. It delivers a luminous flux of 370 lumens at a power consumption of 5.2 watts and emits neutral white light at 4000 Kelvin. The beam angle is 110 degrees, allowing for uniform illumination. The housing is made of aluminium and plastic and measures 30 cm in length, 12 cm in width, and 4 cm in height. The luminaire is rated IP44 for protection against splashing water, making it suitable for damp environments. The DORISA 30 WL has a declared service life of 50,000 hours and is designed for easy wall mounting.



Item no.	1011757
Number of different light outlets	1
IP Code	IP44
Assembly	Surface
Assembly details	Wall,
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	120 mA
Safety class	II
Wattage	5 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	83.0
Number of luminaires at LS C16A	83.0
Level of inrush current	7.44 A
Duration of inrush current	121 µs
Beam angle	110°
Color	black
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	0
Length	30 cm
Width	12 cm
Height	4 cm
Net weight	0.21 kg
Gross weight	0.36 kg
BIG WHITE Page	320