


# BIMA 2.0 1PH., SINGLE, QPAR51

**BIMA 2.0, 1~ spot, SINGLE, QPAR51, 1 x 10 W, white**

The BIMA 2.0 1~ Spot is a single luminaire with a QPAR51 base and a power rating of 10 watts, designed for mounting on ceiling track systems. This luminaire is suitable for indoor use where targeted lighting is required. The housing is made of aluminium and plastic, measuring 10.9 cm in length, 8 cm in width, and 7.2 cm in height. The IP20 protection rating provides protection against solid foreign objects, while the impact resistance corresponds to IK02 class. This luminaire is designed for use in electrical 1-PHASE track systems and allows flexible positioning of the light beam.




## Recommended light bulbs

| | |
|---|---|
| **1005079** | LED lightbulb QPAR51, GU10, 3000 K, white |
| **1012469** | LED PAR16 Smart, GU10, Tunable White, Zigbee |

| | |
|---|---|
| **Item no.** | 1011760 |
| **Socket** | GU10 |
| **Number of sockets** | 1 |
| **Tilt range** | 90° |
| **Horizontal rotation range** | 350° |
| **IP Code** | IP20 |
| **Impact resistance class** | IK02 |
| **Assembly** | Track |
| **Assembly details** | Ceiling, |
| **Primary nominal voltage** | 220-240V ~ 50/60Hz |
| **Safety class** | II |
| **Wattage** | 10 W |
| **Minimum ambient temperature** | -20°C |
| **Maximum ambient temperature** | 40°C |
| **Color** | white |
| **Length** | 10.9 cm |
| **Width** | 8 cm |
| **Height** | 7.2 cm |
| **Net weight** | 0.17 kg |
| **Gross weight** | 0.24 kg |
| **BIG WHITE Page** | 503 |

## Accessories

| | |
|---|---|
| **1011749** | ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black |
| **1011750** | ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white |
| **1011751** | ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold |
| **1011752** | ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper |