


BIMA 2.0 1PH., DOUBLE, QPAR51

BIMA 2.0, 1~ spot, DOUBLE, QPAR51, 2 x 10 W, black

The BIMA 2.0 is a 1-phasiger DOUBLE spot with a QPAR51 base, designed for mounting on ceiling track systems. This luminaire is suitable for indoor use, for example in showrooms, retail environments, or office spaces where targeted accent lighting is desired. The housing is made of aluminium and plastic, providing a robust yet compact design. With a product width of 12.7 cm, a length of 8.3 cm, and a height of 7.2 cm, the spot is space-saving. The IP20 protection rating safeguards against contact and solid foreign objects, while the impact resistance corresponds to IK02 class. The luminaire is equipped with two 10-watt lamps, offering a professional solution for flexible lighting accents in various indoor applications.



Recommended light bulbs

1005080	LED lightbulb QPAR51, GU10, 3000 K, black
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Item no.	1011761
Socket	GU10
Number of sockets	2
Tilt range	90°
Horizontal rotation range	350°
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Ceiling,
Primary nominal voltage	220-240V ~ 50/60Hz
Safety class	II
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Color	black
Length	8.3 cm
Width	12.7 cm
Height	7.2 cm
Net weight	0.29 kg
Gross weight	0.36 kg
BIG WHITE Page	503

Accessories

1011749	ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black
1011750	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white
1011751	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold
1011752	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper