


BIMA 2.0 3PH., SINGLE, QPAR51

BIMA 2.0, 3~ spot, SINGLE, QPAR51, 1 x 10 W, black

The BIMA 2.0 3~ Spot is a three-phase single luminaire with a QPAR51 socket and a power rating of 10 watts. This luminaire is designed for mounting in ceiling track systems and is suitable for indoor use. The housing is made of aluminium and plastic, ensuring a compact and robust construction. With dimensions of approximately 8.2 cm in length, 8.1 cm in width, and 8.1 cm in height, the spot is space-saving in design. The luminaire has an IP20 protection rating and an IK02 impact resistance class, making it suitable for typical use in protected indoor areas.



Recommended light bulbs

1005080	LED lightbulb QPAR51, GU10, 3000 K, black
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Item no.	1011763
Socket	GU10
Number of sockets	1
Tilt range	90°
Horizontal rotation range	350°
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Ceiling,
Primary nominal voltage	220-240V ~ 50/60Hz
Safety class	II
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Color	black
Length	8.2 cm
Width	8.1 cm
Height	8.1 cm
Net weight	0.18 kg
Gross weight	0.26 kg
BIG WHITE Page	563

Accessories

1011749	ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black
1011750	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white
1011751	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold
1011752	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper