


BIMA 2.0 3PH., SINGLE, QPAR51

BIMA 2.0, 3~ spot, SINGLE, QPAR51, 1 x 10 W, white

The BIMA 2.0 3~ Spot is a single luminaire with a QPAR51 socket and a power rating of 10 watts, designed for mounting on ceiling track systems. The housing is made of aluminium and plastic, measuring approximately 8.2 cm in length and 8.1 cm in both width and height. With an IP20 protection rating, the luminaire is suitable for use in dry indoor environments. The impact resistance is classified as IK02, providing basic protection against mechanical impacts. This lighting system is aimed at installers and specialist retailers who require a flexible and compact spotlight solution for indoor use.



Recommended light bulbs

1005079	LED lightbulb QPAR51, GU10, 3000 K, white
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Item no.	1011764
Socket	GU10
Number of sockets	1
Tilt range	90°
Horizontal rotation range	350°
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Ceiling,
Primary nominal voltage	220-240V ~ 50/60Hz
Safety class	II
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Color	white
Length	8.2 cm
Width	8.1 cm
Height	8.1 cm
Net weight	0.18 kg
Gross weight	0.26 kg
BIG WHITE Page	563

Accessories

1011749	ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black
1011750	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white
1011751	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold
1011752	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper