


BIMA 2.0 3PH., DOUBLE, QPAR51

BIMA 2.0, 3~ spot, DOUBLE, QPAR51, 2 x 10 W, black

The BIMA 2.0 3~ Spot is a two-flame spotlight with a QPAR51 socket, designed for mounting on ceiling track systems. Each lamp has a power rating of 10 watts. The housing is made of aluminium and plastic, ensuring a robust yet functional construction. With compact dimensions of 12.7 cm width, 8.2 cm length, and 8.1 cm height, the device is suitable for indoor use. The luminaire features an IP20 protection rating and IK02 impact resistance, protecting it against the ingress of solid foreign objects and minor mechanical impacts.



Recommended light bulbs

1005080	LED lightbulb QPAR51, GU10, 3000 K, black
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Item no.	1011765
Socket	GU10
Number of sockets	2
Tilt range	90°
Horizontal rotation range	350°
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Ceiling,
Primary nominal voltage	220-240V ~ 50/60Hz
Safety class	II
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Color	black
Length	8.2 cm
Width	12.7 cm
Height	8.1 cm
Net weight	0.3 kg
Gross weight	0.38 kg
BIG WHITE Page	563

Accessories

1011749	ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black
1011750	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white
1011751	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold
1011752	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper